

# BCI GROUP NUMBERS, DIMENSIONAL SPECIFICATIONS AND RATINGS

BCI Group Number	Maximum Overall Dimensions						Post/Terminal	Assembly Figure No.	O.E. Performance Ranges	
	Millimeters			Inches					Cold Cranking Performance Amps. @ 0° F (-18° C)	Reserve Capacity Minutes @ 80° F (27° C)
	L	W	H	L	W	H				
<b>PASSENGER CAR AND LIGHT COMMERCIAL BATTERIES 12-VOLT (6 CELLS) Continued</b>										
59	255	193	196	10 1/16	7 11/16	7 3/4	A	21	540-590	100
60	332	160	225	13 1/16	6 5/16	8 7/8	A	12	225-730	65-115
61	192	162	225	7 9/16	6 3/8	8 7/8	A	20	310	60
62	225	162	225	8 7/8	6 3/8	8 7/8	A	20	310-450	75
63	258	162	225	10 3/16	6 3/8	8 7/8	A	20	450	90
64	296	162	225	11 5/8	6 3/8	8 7/8	A	20	475-535	105-120
65	306	192	192	12 1/16	7 9/16	7 9/16	A	21	600-850	130-165
66	306	192	194	12 1/16	7 9/16	7 11/16	A	13	650-750	130-140
67R	231	175	176	9 1/8	6 15/16	6 15/16	A	39	390	65
70	208	180	186	8 3/16	7 1/16	7 5/16	S	17	250-525	60-80
71	208	179	216	8 3/16	7 1/16	8 1/2	S	17	275-450	75-90
72	230	179	210	9 1/16	7 1/16	8 1/4	S	17	275-430	60-90
73	230	179	216	9 1/16	7 1/16	8 1/2	S	17	425-500	80-115
74	260	184	222	10 1/4	7 1/4	8 3/4	S	17	265-550	75-140
75	230	180	186 <sup>Ⓞ</sup>	9 1/16	7 1/16	7 5/16 <sup>Ⓞ</sup>	S	17	245-690	90
76	334	179	216	13 1/8	7 1/16	8 1/2	S	17	750-1075	150-175
77	306	184	222	12 1/16	7 1/4	8 3/4	A	17	350-465	107-110
78	260	180	186	10 1/4	7 1/16	7 5/16	S	17	465-800	105-115
79	307	179	188	12 1/16	7 1/16	7 3/8	S	35	800-840	140
85	230	173	203	9 1/16	6 13/16	8	A	11	430-630	90
86	230	173	203	9 1/16	6 13/16	8	A	10	430-640	90
90	242	175	175	9 9/16	6 15/16	6 15/16	A1,A2	24	450-650	80
91	278	175	175	11	6 15/16	6 15/16	A1,A2	24	520-700	100
92	315	175	175	12 7/16	6 15/16	6 15/16	A1,A2	24	575-720	130
93	353	175	175	13 15/16	6 15/16	6 15/16	A1,A2	24	600-800	150
94R	315	175	190	12 7/16	6 15/16	7 1/2	A1,A2	24	620-790	135
95R	394	175	190	15 9/16	6 15/16	7 1/2	A1,A2	24	760-950	190
96R	242	175	175	9 1/2	6 15/16	6 15/16	A,A1	15	500-590	95
97R	252	175	190	9 15/16	6 15/16	7 1/2	A1,A2	15	575	90
98R	283	175	190	11 1/8	6 15/16	7 1/2	A1,A2	15	620-760	120
99	207	175	175	8 1/8	6 15/16	6 15/16	A1	34	360	50
99R <sup>Ⓞ</sup>	210	175	175	8 5/16	6 15/16	6 15/16	A1	24	470	55-75
100	260	179	188	10 1/4	7 1/16	7 3/8	S	35	770	115
101	260	179	170	10 1/4	7 1/16	6 11/16	S	17	540	115
121R	208	177	215	8 1/4	7	8 1/2	A	11H	500-550	85
124R	262	177	218	10 3/8	7	8 5/8	A	11H	500-660	110
151R	188	125	225	7 7/16	4 15/16	8 7/8	A	28	270-335	55

**NOTES:**

- Ⓞ Rod End Types — Extend top ledge with holes for holddown bolts.
- Ⓞ Not in application section but still manufactured.
- Ⓞ Maximum height dimension shown includes batteries with raised quarter cover design. Flat-top design model height (minus quarter covers) reduced by approximately 3/8 inch (10 mm).